Energy Management Solutions Liquid Energy Specialists

Large Scale Storage Solutions Your Liquid Energy Solutions Overview

Available from 9000 to 28 000 litres

Keeping your Business **Growing**

kingspanenergymanagement.com



Growing through Partnership


Kingspan

The Kingspan group is a dynamic, diverse business, with a global reach. We are the global leader in high performance insulation and building envelope solutions. Improving building performance, construction methods and ultimately people's lives - that's what drives our teams across the world.

Operating in over 80 countries, we deliver pioneering technology, design and manufacturing, backed by a worldwide distribution network and local experienced sales and customer service teams. As a global leader, we understand your requirements and are driven to design and deliver innovations that exceed your expectations, again and again.

Kingspan brings you the confidence of quality and support over the lifetime of your product and beyond.

Our comprehensive portfolio of energy management solutions will meet all your business's fretiliser, water, diesel, AdBlue® and agri storage needs.





212Manufacturing Facilities

+22 000

Countries

+80



6



AdBlue® Single Skin Tanks **Water** Single Skin Tanks



Steel Tank construction corrodes over time

Key Points



Superior, Flexible Construction

One solid piece – not welded, glued or combined. Superior impact resistance to GRP



Purity High quality, virgin Polyethylene guarantees strength and durability



Peace of Mind 10 year guarantee* on the tank and 2 years on equipment



Smart Monitoring Product levels monitored and available 24/7, options to keep in control locally or through

the Kingspan Connect platform



Corossion Free No unsightly rust or degradation of storage like with steel



Maintenance Free No repainting, contamination risk, leakage or other issues



Weatherproof Resistant to harsh weather conditions, and are UV stabilised



Easily transported Designed to fit into regular transport options to decrease cost



Easy Installation Easily installed and moved (when drained) with existing farm equipment. Free standing, no tie down options available



Trustworthy Quality Manufactured to ISO 9001:2015 certified standards



*5 years warranty on 9000 and 15 000 I tanks. The warranty applies to the product used as specified in the manufacturer's instructions.

AgriMaster S® The complete Liquid Fertilizer storage tank range is available with single-skinned construction.

AgriMaster S[®] Equipment options 9000 - 28 000 Litre


AgriMaster S[®] - Single Skin Tanks Capacity: 9000 L, 15 000 L, 22 000 L, 28 000 Ĺ

stainless steel ball valve > 2" (or 3") feed nozzle in 9000 L

AgriMaster S[®] - Single Skin Tanks Capacity: 22 000 L, 28 000 L

- > Access lid 22"
- > Access lid 22" (16" in 9000 L tank) > 2" (or 3") bottom outlet fitted with > 2" (or 3") bottom outlet fitted with
 - stainless steel ball valve
 - Ventilation outlet







AquaBank® Your best solution for water storage.

AquaBank® Equipment options 15 000 - 28 000 Litre

Single Skin Tanks

- > Access lid 22"
- > 2" bottom outlet fitted with
- plated brass ball valve
- › Ventilation outlet



Model Selector

All dimensions are approximate. The dimensions may vary due to manufacturing process variations and/or environmental conditions. AquaBank® tanks are not designed for the drinking water storage.

AquaBank® - Single Skin Tanks						
Capacity		15 000 litres (N)	15 000 litres	22 000 litres		
Dimensions	Diameter	2 950 mm	2 350 mm	2 480 mm		
	Height	2 750 mm	4 325 mm	5 265 mm		

Product Codes			
2" ball valve	0600400	1054910	0672001
3" ball valve	0600401	-	0672011

Model Selector

Dimensions may vary within a small parameter due to manufacturing process variations or environmental conditions.

AgriMaster S [®] - Single Skin Tanks						
Capacity		9000 litres	15 000 litres (N)	15 000 litres	22 000 litres	28 000 litres
Dimensions	Diameter	2300 mm	2 950 mm	2 350 mm	2 480 mm	2 480 mm
	Diameter	2 900 mm	2 750 mm	4 325 mm	5 265 mm	6 190 mm

Product Codes					
2" ball valve	0282001	0280001	1054901	0670015	0670017
3" ball valve	0282002	0280002	-	0670035	0670037
2" ball valve + GSM	-	0280016	-	0670055	0670057
3" ball valve + GSM	-	0280017	-	0670075	0670077
2" ball valve + filling line	-	-	-	0670115	0670117
3" ball valve + filling line	-	-	-	0670135	0670137



Advantages of the black-colored design:

- > prevents algae bloom
- > keeps rain water in better condition
- > helps to heat the water

28 000 litres	
2 480 mm	
6 190 mm	

0672003
0672013

BlueMaster® The complete AdBlue[®] storage tank range is available with single-skinned construction.

BlueMaster[®] Equipment options 9000 - 28 0000 Litre

Single Skin Tanks

Capacity: 9000 L, 15 000 L, 22 000 L, 28 000 L

- > Access lid 22" (16" in 9000 L tank)
- > 2" (or 3") bottom outlet fitted with
- stainless steel ball valve > 2" (or 3") feed nozzle in 9000 L
- and 15 000 L tank Ventilation outlet

- Single Skin Tanks Capacity: 22 000 L, 28 000 L
- > Access lid 22"
- > 2" bottom outlet fitted with stainless steel ball valve
- > Ventilation outlet
- > Filling line at working level



Model Selector

Dimensions may vary within a small parameter due to manufacturing process variations or environmental conditions.

BlueMaster® - Single Skin Tanks						
Capacity		9000 litres	15 000 litres (N)	15 000 litres	22 000 litres	28 000 litres
Dimensions	Diameter	2 300 mm	2 950 mm	2 350 mm	2480 mm	2 480 mm
	Height	2 900 mm	2 750 mm	4 325 mm	5 265 mm	6190 mm

Product Codes					
2" ball valve	-	0280005	-	0670095	0670097
2" ball valve + filling line	-	-	-	0670165	0670167

Smart Monitoring Award Winning Monitoring Solutions for Liquid Energy.





Features:

- Notification of leakage, overfilling and low liquid level \rightarrow Buzzer: (93 dB) internally mounted Access to cloud-based software on the Kingspan
- > Control of the automatic filling handle > Liquid status indication displayed in:
- 'litres', 'cm' and '%'

Watchman[®] Radar

Radar precision technology - no drilling necessary, for any stored liquid or solid substances

Features:

- Measurement via radio microwaves
- > Monitoring of tanks up to a height of 6 m > Fast and simple installation without drilling (in a plastic tank)
- > Full control via Kingspan Connect mobile app
- > Access to consumption and substance level data at any time, from any location
- > Built-in gyroscope ensuring 100% measurement accuracy

Watchman[®] LT

modern ultrasonic technology with advanced algorithms

Features:

- > The narrow measuring beam enables install close to the tank walls
- > Short dead band not covered by the measur
 - > Long lifetime of a product

Watchman[®] WAPex

Precise telemetry system for remote GSM tank monitoring

Features:

- > Measurement of liquid level and tank capaci
- Very quick installation
 - > Works with Watchman® LT or pressure probe



platform

connect

updecision making and optimise your business.

- Fuelling memory (max. 10 entries)
- Connect platform and Kingspan Connect mobile app \rightarrow GSM and Wi-Fi connection available
 - > Compatible with ultrasonic sensor Watchman® Sonic Plus Advanced

- > Minimum 5 years of battery life thanks to NB-IoT connectivity
- > Quick setup via dedicated mobile app
- > GPS monitoring of tank location including mobile tanks
- > Precision measurement up to 1 cm monitoring of liquids and solids stored in any tank

Precise and non-contact measurement for local tank level monitoring, developed by combining

ation	>	Sensor protection in compliance with standard IP68
	>	PVDF housing resistant to chemicals and acids
rement	>	99.8 % measurement accuracy even in demanding
		environmental conditions

ity	>	Optional GPS
	>	Robust housing
е	>	Waterproof

Contact Details

Visit kingspanenergymanagement.com to learn more about our products and services in over 80 countries. For local information on the Large Scale Storage Solutions please contact:

UK

E: tankinfo@kingspan.co.uk Tel: +44 (0) 28 3836 4444

Ireland E: tankinfo@kingspan.ie Tel: +353 42 969 0022

Netherlands

E: info@kingspan-env.nl Tel: +31 344 760050

Sweden

E: tank@kingspan.se Tel: +48 61 660 94 46

Poland E: zbiorniki@kingspan.pl Tel: +48 61 814 44 00

Global Head Office

180 Gilford Road Portadown Co. Armagh BT63 5LF United Kingdom Tel: +44 (0) 28 3836 4444

New Zealand E: tankinfo@kingspan.co.nz Tel: +44 (0) 28 3836 4444

North America E: TalkToUs@kingspan.com

France E: cuve@kingspan.fr Tel: +33 9 75 18 76 49

Belgium E: info@kingspan-env.be Tel: +32 51 48 51 42

Germany E: tank@kingspan.de Tel: +49 6102 3686700

European Office

5 Topolowa St. . 62-090 Rokietnica Poland Tel: +48 61 814 44 00 **Czech Republic** E: nadrze@kingspan.cz Tel: +420 725 114 555

Finland E: tankinfo@kingspan.com Tel: +48 61 660 94 46

Norway E: tank@kingspan.no Tel: +48 61 660 94 46

Denmark E: titan@kingspan.com Tel: +48 61 660 94 46

Middle East E: tankinfo@kingspan.me Tel: +44 (0) 28 3836 4444



Kingspan Water & Energy manufacturing processes meet the restrictive ISO standards:

- ISO 9001:2015 Quality Management System
- ISO 14001:2015 Environmental Management System
- ISO 37301:2021 Compliance Management System
- ISO 45001:2018 Occupational Health and Safety Management System
- Follow Kingspan Water & Energy on:







@kingspanwaterenergy

kingspanenergymanagement.com

We take every care to ensure that the information in this document is accurate at the point of publication. Specification We take every care to ensure that the information in this document is accurate at the point of publication. Specification may vary (within a small parameter) due to manufacturing process variations or environmental conditions. All images are for illustration purposes only and should not be taken as binding. The actual product may vary, and specification/ dimensions/colour/other attributes may differ. To ensure you are viewing the most recent and accurate product information, please visit kingspan.com. @Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries. All rights reserved. Registered Office: 180 Gilford Road, Portadown, Co. Armagh, BT63 5LF. VAT GB412 5124 03. European Office: 5 Topolowa St., 62-090 Rokietnica, Poland. VAT PL779 20 57 260.



