



2500 L



5000 L

AdBlue® Storage
and Dispensing Tanks

DESO



AdBlue® STORAGE AND DISPENSING TANKS

All Deso AdBlue® tanks are manufactured to have a double skin to protect the environment against leaks, ground contamination and ensure your AdBlue® remains pure.

Our AdBlue® tanks have been designed with companies that run vehicles with SCR technology, and therefore have the need for AdBlue®, such as cars, trains, buses, freight and tractors. Our products are highly resistant to mechanical damage and external factors such as UV light, temperature and moisture.

10 year tank and two year parts guarantee.

Our guarantee applies to the products used in accordance with the manufacturer's operating manual.



Digital flow-meter K24



Submersible pump 230V AC



Selected accessories

- 1 Digital flow-meter K24
- 2 Submersible pump 230V AC
- 3 Thermostat controlled electric heating
- 4 Automatic nozzle
- 5 Distribution hose 6m
- 6 Inspection lid 4" in tank 2500 L and 8" in tank 5000 L
- 7 Fluid level gauge meter
- 8 Control box
- 9 Connection box

Options:

PU insulation of inner tank

Symbol	Nominal Capacity [L]	Diameter [mm]	Length [mm]	Height [mm]	Width [mm]
BBMD2500-235	2500	-	2310	1950	1550
BBMD5000-235	5000	2460	2460	2050	2460
BBMD2500-235I	2500	-	2310	1950	1550
BBMD5000-235I	5000	2460	2460	2050	2460

Available combinations per truck:

- 4 x 5000 and 2 x 2500
- 3 x 5000 and 4 x 2500
- 2 x 5000 and 5 x 2500

Product dimensions may differ in range +/- 1%.

DESO ENGINEERING LTD

Slade Way, Roughmoor Industrial Estate, Williton, Somerset. TA4 4TB

Tel: 01984 632 026, Fax: 01984 634 267,

Tel.: +48 605 551 850 Email: marek.reich@kingspan.com

www.zbiornikideso.pl

DESO